

# Safety Data Sheet

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product Name:** Acetone Group F  
**Product Code:** SPB0000

**Application of the mixture:** Inflammable products: setting lotions, hair lacquers, pump sprays and other styling products

**CAS No:** 67-64-1

### Company Name and Address:

Bellitas Ltd,  
Unit 12 Prospect Drive,  
Britannia Enterprise Park,  
Lichfield,  
Staffs.  
WS14 9UX

**Emergency Telephone No: +44 (0) 1543 416611**

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to EC 1272/2008  
H225 Highly flammable liquid and vapour  
H319 Causes serious eye irritation  
H312+H332 Harmful in contact with skin or if inhaled

The full text for all Risk Phrases and Hazard Statements are displayed in section 16

### 2.2 Label Elements



GHS02: Flammable



GHS07: Harmful

**Signal word:** DANGER

### Hazard Statements:

H225 Highly flammable liquid and vapour  
H319 Causes serious eye irritation  
H312+H332 Harmful in contact with skin or if inhaled

### Precautionary Statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P403: Store in a well ventilated place.  
P337+313: If eye irritation persists get medical advice/attention.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable – product is a mixture

### 3.2 Mixtures/Ingredients

Acetone.

Name/Form.	CAS / EC No.	Concentration	Classification
M8010	67-64-1 200-662-2	>60%w/w	H225 H319 H312+H332
Main Active(s)	Acetone.		

The full text for all R-Phrases and Hazard Statements are displayed in section 16

# Safety Data Sheet

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**Inhalation** Breath fresh air, if dizziness or shortness of breath persists seek medical advice.  
**Skin Contact** Wash well with water; if irritation persist seek medical advice  
**Eye Contact** Wash well with water; if irritation persists seek medical advice.

**Accidental Ingestion** Do not induce vomiting, drink copious amounts of water. Seek medical help.

### 4.2 Most important symptoms and effects, both acute and delayed

**Inhalation** Symptoms unlikely from small amounts, but inhalation of large amounts may cause headaches, dizziness, unconsciousness  
**Skin Contact** Prolonged skin contact may cause drying of the skin  
**Eye Contact** If liquid gets into the eyes it may cause redness, stinging, watering of the eye  
**Ingestion** Ingestion of the liquid may cause irritation to the throat and mouth, and symptoms similar to inhalation

### 4.3 Indication of any immediate and any special treatment needed

**Immediate / special treatment** Symptomatic treatment as required

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Use:** Extinguish with sand, earth, water spray or powder extinguisher  
**Avoid:** High pressure water jet as this may spread the fire

### 5.2 Special Hazards arising from the substance or mixture

Unusual fire and explosion hazards  
The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures  
Formation of toxic gases is possible during heating or in the case of a fire: Carbon monoxide (CO).

### 5.3 Advice for firefighters

Protective equipment for firefighters  
Wear self-contained breathing apparatus and full protective clothing. Keep all unnecessary people away  
Fire water run off must not be allowed to contaminate ground or enter drains, sewers or water courses. Provide bunding against fire water

### Additional information

Cool endangered receptacles with water spray

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. Wear gloves when handling spillages.

### 6.2 Environmental precautions

Avoid spreading of the material. Contain spillages with sand, earth or suitable inert absorbent material. Prevent further spillages.  
Do not allow to penetrate the ground/soil, enter drains or water courses. Cover drains. In the case of contamination of water courses or sewers advise the Environmental Agency, fire brigade and police.

### 6.3 Methods and materials for containment and cleaning up

Absorb with liquid binding material, vermiculite, sand, earth or suitable inert absorbent material.  
Rinse site with copious amounts of water, which should not be allowed into drains, sewers or watercourses  
Ensure adequate ventilation

### 6.4 Reference to other sections

See section 7 for information on safe handling  
See section 8 for information on protective equipment  
See section 13 for disposal information

# Safety Data Sheet

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Eye wash facilities and emergency shower must be available when handling this product. Avoid spilling, contact with the eyes and prolonged contact with the skin. Do not breathe the vapour or fumes. Use suitable protective clothing (see section 8). Wash thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Store in its original, tightly closed, labelled container in a cool, well ventilated area, away from heat, sparks and any other sources of ignition. Keep out of reach of children and animals. Not suitable for storage in aluminium containers.

#### Incompatibilities

Store away from oxidising agents.

Store away from alkalis (caustic solution).

Store away from acids.

### 7.3 Specific end use(s)

No special precautions.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Workplace exposure limits

Name	Std	TWA 8 hour exposure limit	STEL 15 minute exposure limit	Source/Type
<b>DNELS</b>		Worker		Consumer
		Systemic effects		Systemic effects
Human oral		none stated		
Human dermal				
Human inhalation				
Human inhalation				

#### PNECS

PNEC Aqua (Freshwater)

PNEC Aqua (Marine)

PNEC Sediment

PNEC Soil

### 8.2 Exposure controls

Engineering measures	Provide eyewash station.
Respiratory protection	If ventilation is insufficient suitable respiratory equipment must be provided.
Hand protection	For prolonged contact with the product, suitable protective gloves conforming to EN374 should be worn. Seek recommendations from manufacturer or supplier.
Eye protection	Contact lenses should not be worn when working with this chemical. Wear approved safety goggles.
Skin protection	Minimise all forms of skin contact. Wash promptly if skin becomes contaminated. Wear suitable protective clothing. Promptly remove non-impervious clothing that becomes contaminated. Launder overalls and under garments regularly. When using do not eat, drink or smoke.
Other protective & hygiene measures	Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

## SECTION 9: Physical and chemical properties

### 9.1 Information on the basic physical and chemical properties

Appearance	Mobile liquid.
Odour	Fragranced with perfume.
Odour threshold	Not determined
pH value	pH 6.0 - 8.0
Solubility in water	Soluble or dispersible in water
Initial boiling point/boiling range °C	78°C (ethanol)
Melting Point / range °C	None specified
Flash point °C	-18°Ccc
Upper/lower flammability limits	Typically 2-12%
Vapour pressure at 20°C	None specified
Vapour density at 20°C	1
Auto ignition temperature °C	None specified
Alcohol content	>60%w/w
Specific gravity	0.83 - 0.97
Viscosity at 20°C	Mobile liquid

### 9.2 Other information

None

# Safety Data Sheet

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not considered to be reactive

### 10.2 Chemical stability

Stable under normal conditions and storage. See section 7

### 10.3 Possibility of hazardous reactions

Explosive reactions with oxidising agents such as calcium carbonate and or peroxides. Reacts with strong oxidising agents. Reacts with strong acids.

### 10.4 Conditions to avoid

High temperatures, flames and other sources of ignition.

### 10.5 Incompatible materials

Strong oxidising agents, strong acids, Al, amines, alkalis.

### 10.6 Hazardous decomposition products

Toxic gases or vapours, carbon monoxide and carbon dioxide.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

Acute toxicity                      This product has not been subjected to toxicity testing.

Inhalation                      In high concentrations vapours may cause headache, fatigue, dizziness and nausea

Skin contact                      Prolonged and frequent exposure may cause skin dryness and cracking

Ingestion                      Gastrointestinal symptoms, including upset stomach

Eye contact                      Irritating to the eyes

**Comments**                      This product has been assessed as safe to use under normal conditions of use and according to instructions.

## SECTION 12: Ecological information

This product has not been subjected to toxicological testing. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

This product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment

### 12.1 Toxicity

Toxicity to fish                      No data available.

Toxicity to invertebrates                      No data available.

Toxicity to algae                      No data available.

### 12.2 Persistence and degradability

Readily biodegradable.

### 12.3 Bioaccumulation

No data available.

### 12.4 Mobility in soil

No further relevant information available

### 12.5 Results of PBT and vPvB assessment

Not applicable

### 12.6 Other adverse effects

No further relevant information available

## SECTION 13: Disposal considerations

Do allow the product to reach the sewerage system or waterways.

Empty containers may contain residual product and flammable vapours. Keep away from sparks, heat and sources of ignition.

Product is hazardous waste. Disposal must be by means of a licenced waste contractor.

# Safety Data Sheet

## SECTION 14: Transport information

### 14.1 UN number

UN No. (ADR/RID/IMDG/IATA)

UN1090

### 14.2 UN proper shipping name

Acetone

### 14.3 Transport hazard class(es)

ADR, IMDG, IATA

3 Flammable liquids  
3 Label Class

### 14.4 Packing group

II (ADR/RID/AND/IMDG/ICAO,IATA)

### 14.5 Environmental hazards

Marine pollutant

No

### 14.6 Special precautions for user

Danger code (Kemlar)/hazard no. (ADR)

33

EMS no.

F-E, S-D

Stowage category

B

Tunnel restriction code

D/E

### 14.7 Transport in bulk according to annex II of Marpol and the IBC Code

Not applicable

### 14.8 Additional information

Limited quantities (LQ)

1 Litre(s)

EC N°

200-662-2

## SECTION 15: Regulatory information

### 15.1 Safety, health and environment regulations/legislation specific for the substance or mixture

All components are listed as existing substances in Europe

### 15.2 Chemical safety assessment

A product Safety Assessment has been carried out in accordance with EC 1223/2009, Cosmetic Product Safety Regulations.

## SECTION 16: Other information

Classification of the mixture is in general based on calculation method using substance data, as required by (EC) 1272/2008

### Abbreviations and acronyms used in the safety data sheet

CAS No	Chemical Abstracts Service number
DNEL	Derived No-Effect Level
EC	European Community
EEC	European Economic Community
EMS No	Emergency Response Procedure number
Eye Irrit.	Eye Irritant
Flam. Liq.	Flammable Liquid
hPa	1 hPa = 100 Pa (Pascal)
LC50	Lethal Concentration, 50%
LD50	Lethal Dose, 50%
PBT	Persistent, Bio accumulative and Toxic
PNEC	Predicted No-Effect Concentration
Ppm	Parts Per Million
REACH	Registration, Evaluation, Authorisation and Restrictions of Chemicals
STOT	Specific Target Organ Toxicity
vPvB	Very Persistent and Very Bio accumulative
WEL	Workplace Exposure Limit

### Hazardous and Precautionary Statements in full used in section 2 and 3

#### Hazard Statements:

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

H312+H332 Harmful in contact with skin or if inhaled

#### Precautionary Statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P403: Store in a well ventilated place.

P337+313: If eye irritation persists get medical advice/attention.

Version 20: 1

Issue Date: 06/01/2021

WE BELIEVE THAT THE INFORMATION CONTAINED HEREIN IS CURRENT AS OF THE DATE OF THIS SAFETY DATA SHEET.  
IT IS THE USERS OBLIGATION TO DETERMINE CONDITIONS OF SAFE USE OF THIS PRODUCT.